

URANIA TURBO LD Cod. 1333

DESCRIPTION

Mineral based engine oil. For industrial vehicles with turbo engines of every type and power rating. Also ideal for industrial vehicles with aspirated engines and commercial vehicles. URANIA TURBO LD has been created and developed by FL using the vastest engine experience available today to meet the requirement of Iveco for new generation engines. Moreover it can guarantee a reduction in oil consumption of up to 30%.

CHARACTERISTICS

The main characteristic of URANIA TURBO LD are:
Longer change interval up to 50,000 km and beyond;
Engine protection increased by 50% against pollution or acid components from the combustion of diesel fuels with a high sulphur content.
It also ensures:

- | Maximum protection against wear caused by the continuous engine performance in conditions with heavy loads;
- | Maximum protection against deposits (lacquer, sludge and other pollutants) caused by high running temperatures;
- | Easy cold start, as well as high and constant pressure in the lubricant circuit at all working and climatic temperatures.



As it exceeds the quality requirements of all the European Manufacturers of industrial vehicles, URANIA TURBO LD can be used for turbo-charged or aspirated diesel engines of every type, make and power rating.



ADVICE ON USE

Replacement as indicated by the Manufacturer,
recommended oil changes are:
Up to 20,000 km on vehicles operating under heavy-duty conditions
Up to 50,000 km and beyond on vehicles in road/long distance service.

RECOMMENDED BY

Iveco, Iveco Motors.

APPROVED BY

Mercedes, Volvo, Man, Mack.

TECHNICAL DATA

SAE 15W-40,
IVECO 18-1804 CLASSE T1, CONTRACTUAL TECHNICAL REF. N°1002.A94,
ACEA E3, API CF, MAN M3275, MB-Approval 228.3,
RENAULT VI RD Performance, VOLVO VDS-2