



## Castrol Agri MP 15W-40

Universal tractor oil

### Description

Castrol Agri MP is a universal API GL-4 oil for most types of farm machinery.

### Advantages

- One oil that protects engine, transmission, wet brake, hydraulic and front axles
- One oil reduces inventory, saves money
- Using an advanced formulation, Castrol Agri MP reduces engine wear by up to 30% compared to conventional STOU products

### Typical Characteristics

Name	Method	Units	Agri MP 15W-40
Density @ 15C, Relative	ASTM D1298	g/ml	0.886
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	95
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	13.3
Viscosity Index	ASTM D2270	None	140
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	5000
Viscosity, Brookfield @ -18C	ASTM D2983	mPa.s (cP)	7600
Pour Point	ASTM D97	°C	-42
Flash Point, COC	ASTM D92	°C	226

API GL-4

## Product Performance Claims

API CE/SF

Meets Ford ESN-M2C-159B

JDM J27

MF - M1139

ZF TE-ML 06B, 07B

May be used where Ford M2C134-D

M2C86B and Case MS 1207 is specified

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Agri MP 15W-40

12 Sep 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Ltd, Wakefield House, Pipers Way, Swindon, SN3 1RE, UK

[www.castrol.com](http://www.castrol.com)