



Agri MP Plus 10W-30

Super universal tractor oil

Application

One oil that delivers high performance & protection for engine, transmission, wet brake, hydraulic and front axles.

Approval Status

- API CF-4/CE/SF.
- API GL-4.
- M1144 approved.
- M1141, M1139, M1135.
- JDM J27 & J20C.
- Ford M2C 86A, 134B & C, 159B.
- Case MS1207.
- ZF TE-ML 06B/07B.
- NFE 48603 HV.
- DIN 51524/3 HVLP.

Features and Benefits

- One oil simplifies servicing, avoids misapplication.
- One oil reduces inventory, saves money.
- Excellent cold start protection reduces engine wear.

Technical Data

Name	Method	Units	Agri MP Plus 10W-30
Density @ 15°C, Relative	ISO 3675 / ASTM D1298	g/ml	0.889
Viscosity, Kinematic 40°C	ISO 3104 / ASTM D445	mm ² /s	73.3
Viscosity, Kinematic 100°C	ISO 3104 / ASTM D445	mm ² /s	11.0
Viscosity Index	ISO 2909 / ASTM D2270		143
Viscosity, CCS -25°C	ASTM D5293	mPa.s (cP)	6600
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.7
Flash Point, COC	ISO 2592 / ASTM D92	°C	220
Pour Point	ISO 3016 / ASTM D97	°C	-36
Ash, Sulphated	ISO 3687 / ASTM D874	% wt	1.5

The above figures are typical of those with normal production tolerance and do not constitute a specification.

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Agri MP Plus 10W-30

29 Aug 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Australia Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1854

Dubai City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

Norway Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43

Singapore Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

United Kingdom The Innovation Centre, Aberdeen, AB23 8GX, UK. Customer Service Number +44 (0)1224 258 980

USA 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157

www.castrol.com/offshore

